
# Squeegees

**Squeegee characteristics: blade material,** flexibility, angle of attack and mounting have an important effect on process control when stencil printing. And matching the squeegee to the application is made easier by DEK's comprehensive range of polyurethane and stainless steel blades, bonded or clamped mounting options, and a choice of 45° or 60° printing angle.



Polyurethane Squeegees Polyurethane squeegees satisfy single thickness or stepped stencil applications, according to material hardness. Choose harder squeegees, durometer 97 and above, for durable, low abrasion performance with single thickness stencils. DEK squeegees are



maximum. Step stencil applications may require softer squeegee material; choose polyurethane from 70 to 94 durometer. DEK polyurethane squeegees can be reground to maintain a keen edge throughout a lifetime. DEK also utilizes polyurethane for PumpPrint squeegees, specially designed for the high-speed application of glue for bottom side chipattach. Soft polyurethane is also the material of choice for traditional mesh-andemulsion screen printing applications.

Stainless Steel Squeegees Lower-cost stainless steel squeegees sustain higher squeegee pressures and are ideal for boards featuring a mix of large and fine pitch components, or where panel flatness cannot be assured. With this wider pressure window, consistency is outstanding and wear is minimal. Stainless steel squeegees should be handled carefully in order to avoid accidental damage.

Bonded/Clamped Squeegees Mounting options include bonding or clamping. Clamping allows squeegees to be interchanged easily, enabling adjustment of blade flexibility and durometer to suit the application.

Clamping is particularly suitable for use with metal and composite blades. The bonded squeegee assembly guarantees an ultra straight blade edge when using high durometer polyurethane squeegees. Set up time is also reduced.

The bonded assembly allows manufacturers to exploit the advantages of the polyurethane material, including use of a greater paste bead through the enlarged blade face and lower pressure settings resulting from the ground printing edge. This is accompanied by a significant increase in squeegee life.

Only available for DEK screen printers.



# **Metal Squeegees**

## Metal Clamped Squeegees 60° ∼ 6mm Overhang

Order Code	Size	UOM
SQA310	170mm	Pair
SQA311	200mm	Pair
SQA312	250mm	Pair
SQA313	300mm	Pair
SQA314	350mm	Pair
SQA315	400mm	Pair
SQA316	440mm	Pair
SQA317	483mm	Pair
SQA318	510mm	Pair
SQA319	535mm	Pair



#### Metal Clamped Squeegees 60° ~ 15mm Overhang

Order Code	Size	UOM (Unit of Manufacture)
SQA300	170mm	Pair
SQA301	200mm	Pair
SQA302	250mm	Pair
SQA303	300mm	Pair
SQA304	350mm	Pair
SQA305	400mm	Pair
SQA306	440mm	Pair
SQA307	483mm	Pair
SQA308	510mm	Pair
SQA309	535mm	Pair

#### **60° Replacement Blades**

Order Code	Size	UOM
129924	170mm	Each
129925	200mm	Each
129584	250mm	Each
129585	300mm	Each
129926	350mm	Each
129586	400mm	Each
129927	440mm	Each
129587	483mm	Each
129588	510mm	Each
129928	535mm	Each



## **Metal Squeegees**

## 45° Metal Clamped Squeegees

Order Code	Size	UOM (Unit of Manufacture)
SQA350	170mm	Pair
SQA351	200mm	Pair
SQA352	250mm	Pair
SQA353	300mm	Pair
SQA354	350mm	Pair
SQA355	400mm	Pair
SQA356	440mm	Pair
SQA357	483mm	Pair
SQA358	510mm	Pair
SQA359	535mm	Pair



#### 45° Replacement Blades

Order Code	Size	UOM
133601	170mm	Each
133602	200mm	Each
133603	250mm	Each
133604	300mm	Each
133605	350mm	Each
133606	400mm	Each
133607	440mm	Each
133608	483mm	Each
133609	510mm	Each
133610	535mm	Each



## **Metal Squeegees**

#### Lead Free Metal Clamped Squeegees 60° ~ 6mm Overhang

- Anodised Green
- Chromium Blades (CrN) ~ 1.5 microns

Order Code	Size	UOM
SQAG311	200mm	Pair
SQAG312	250mm	Pair
SQAG313	300mm	Pair
SQAG314	350mm	Pair
SQAG315	400mm	Pair
SQAG316	440mm	Pair



#### Lead Free Metal Clamped Squeegees 60° ~ 15mm Overhang

- Anodised Green
- Chromium Blades (CrN) ~ 1.5 microns

Order Code	Size	UOM
SQAG301	200mm	Pair
SQAG302	250mm	Pair
SQAG303	300mm	Pair
SQAG304	350mm	Pair
SQAG305	400mm	Pair
SQAG306	440mm	Pair

#### **Lead Free Replacement Blades**

Order Code	Size	UOM (Unit of Manufacture)
431001	200mm	Each
431002	250mm	Each
431003	300mm	Each
431004	350mm	Each
431005	400mm	Each
431006	440mm	Each



## **Polyurethane Squeegees**

#### Polyurethane Bonded Squeegees Green 70-75 Shore Hardness ~ 45°

Order Code	Size	UOM
SQA248	100mm	Pair
SQA254	150mm	Pair
SQA161	170mm	Pair
SQA167	200mm	Pair
SQA174	250mm	Pair
SQA152	300mm	Pair
SQA185	350mm	Pair
SQA190	400mm	Pair
SQA201	440mm	Pair
SQA210	483mm	Pair
SQA219	510mm	Pair
SQA231	535mm	Pair



#### Polyurethane Bonded Squeegees Green 70-75 Shore Hardness ~ 60°

Order Code	Size	UOM
SQA260	100mm	Pair
SQA266	150mm	Pair
SQA119	170mm	Pair
SQA120	200mm	Pair
SQA139	250mm	Pair
SQA155	300mm	Pair
SQA121	350mm	Pair
SQA196	400mm	Pair
SQA122	440mm	Pair
SQA136	483mm	Pair
SQA225	510mm	Pair
SQA123	535mm	Pair

**ASIA:** China: +86 755 2759 9188, Singapore: +65 6484 7010

**EUROPE:** UK: +44 1305 760760, Germany: +49 6101 5227-0, Hungary: +36 96 512 100

**AMERICAS:** +1 847 368 1155



## **Polyurethane Squeegees**

PumpPrint<sup>™</sup> Squeegees Glue printing with DEK PumpPrint<sup>™</sup> Stencils

Order Code	Size	UOM
SQA455	170mm	Pair
SQA456	200mm	Pair
SQA457	250mm	Pair
SQA458	300mm	Pair
SQA459	350mm	Pair
SQA460	400mm	Pair
SQA461	440mm	Pair
SQA462	483mm	Pair
SQA463	510mm	Pair
SQA464	535mm	Pair





**EUROPE:** UK: +44 1305 760760, Germany: +49 6101 5227-0, Hungary: +36 96 512 100

**AMERICAS:** +1 847 368 1155

